

PS-M672 SERIES

-72/340-360/5BB

MONOCRYSTALLINE SILICON MODULE

Key Features



PROPSOLAR 5BB design module reduce cell series resistance and stress between cell interconnectors improves module reliability and module conversion efficiency



High power output of more than 360W and module efficiency up to 18.55%



Anti-reflective and anti-soiling surface reduces power loss from dirt and dust



Outstanding performance in low-light irradiance environments



Excellent mechanical load resistance: Certified to withstand high wind loads (2400Pa) and snow loads (5400Pa)



High salt and ammonia resistance

Reliable Quality

- Positive power tolerance: 0~+5W
- 100% EL double-inspection ensures modules are defects free
- Modules binned by current to improve system performance
- Potential Induced Degradation (PID) Resistant

Comprehensive Certificates

- IEC 61215, IEC 61730 and CE
- ISO 9001: 2008: Quality management systems



Shanghai Propsolar New Energy Co.,Ltd

Propsolar was founded in May,2010 with professional production of crystal silicon solar cell,Photovoltaic (PV) modules,solar system,solar water pump and solar street light. We specialize in the development and utilization of new energy to provide one stop service and total solution to all global customers.


Contact:

Add: Room 402, No.500 South Xiangyang Road, Shanghai, China. Post code: 200031
Tel : +86 2154658961
Fax: +86 2154658962
Email: sales@propsolar.com
Website: www.propsolar.com



Superior Warranty


- 10-year product warranty
- 25-year linear power output warranty



www.propsolar.com

PS-M672 SERIES -72/340-360/5BB

Engineering Drawings



■ customized cable length available upon request

MECHANICAL PARAMETERS

Cell (mm)	Mono 156.75x156.75
Weight (kg)	21 (approx)
Glass Thickness	4 mm
Dimensions (LxWxH) (mm)	1956x992x40
Cable Cross Section Size (mm ²)	4
No. of Cells and Connections	72 (6x12)
Junction Box	IP67, 3 diodes
Connector	MC4 Compatible
Packaging Configuration	23 Per Pallet

WORKING CONDITIONS

Maximum System Voltage	DC 1000V (IEC)
Operating Temperature	-40°C ~ +85°C
Maximum Series Fuse	15A
Maximum Static Load, Front (e.g., snow and wind)	5400Pa (112 lb/ft ²)
Maximum Static Load, Back (e.g., wind)	2400Pa (50 lb/ft ²)
NOCT	45±2°C
Application Class	Class A

ELECTRICAL PARAMETERS

TYPE	PS-M672 340/5BB	PS-M672 345/5BB	PS-M672 350/5BB	PS-M672 355/5BB	PS-M672 360/5BB
Rated Maximum Power at STC (W)	340	345	350	355	360
Open Circuit Voltage (Voc/V)	46.2	46.7	47.0	47.4	47.7
Maximum Power Voltage (Vmp/V)	38.2	38.5	38.7	38.8	39
Short Circuit Current (Isc/A)	9.50	9.55	9.60	9.65	9.70
Maximum Power Current (Imp/A)	8.90	8.96	9.04	9.14	9.24
Module Efficiency [%]	17.52	17.78	18.03	18.29	18.55
Power Tolerance (W)	-0~+5W				
Temperature Coefficient of Isc (αIsc)	+0.059%/°C				
Temperature Coefficient of Voc (βVoc)	-0.330%/°C				
Temperature Coefficient of Pmax (γPmp)	-0.410%/°C				

STC Irradiance 1000W/m², Cell Temperature 25°C, Air Mass 1.5

NOCT

TYPE	PS-M672 340/5BB	PS-M672 345/5BB	PS-M672 350/5BB	PS-M672 355/5BB	PS-M672 360/5BB
Max Power (Pmax) [W]	253	257	261	264	268
Open Circuit Voltage (Voc) [V]	42.9	43.4	43.7	44.1	44.3
Max Power Voltage (Vmp) [V]	35.4	35.7	35.9	36.0	36.2
Short Circuit Current (Isc) [A]	7.67	7.71	7.75	7.79	7.83
Max Power Current (Imp) [A]	7.15	7.20	7.26	7.34	7.42

Condition Under Normal Operating Cell Temperature, Irradiance of 800 W/m², spectrum AM 1.5, ambient temperature 20°C, wind speed 1 m/s

Electrical data in this catalog do not refer to a single module and they are not part of the offer. They only serve for comparison among different module types.

I-V CURVE

